

www.fel.fujitsu.com



fi-4010CU A4 document scanner

- 3.3ppm colour at 150dpi
- 10ppm mono at 200dpi
- Simplex scanner
- 25 page ADF & Flatbed
- USB1.1
- A6 – A4 scanning
- Adobe Acrobat 5.0 bundled

Adobe®
Acrobat® 5.0 **Bundled!**
for Microsoft® Windows® 98/Me/2000/XP

FUJITSU

THE POSSIBILITIES ARE INFINITE



Fujitsu's fi-4010CU scanner provides a professional office scanning solution for the office and small business market.

The fi-4010CU offers users a cost effective, high speed, high quality scanner to cope with low volume scanning applications. It is an ideal scanner for scanning photographs and graphics, allowing users to scan, copy, email and fax files simply and effectively.

The fi-4010CU is a compact colour scanner able to scan at 3.3 pages per minute in colour (150dpi) through the ADF and 10 pages per minute in black and white at 200dpi.

The fi-4010CU has the ability to scan from A6 size to A4 either through the 25 page capacity ADF or on the flatbed which can be used to scan delicate or bound documents.

The scanner has a USB interface enabling easy installation with straight forward plug and play connection.

The fi-4010CU offers a MTBF of 5,000 hours based on a recommended daily throughput of 500 pages and is designed to offer users exceptional image quality, reliability and performance.

The inclusion of Adobe Acrobat 5.0 software in the fi-4010CU, will allow users to easily convert any document to an Adobe Portable Document format (PDF) file.

fi-4010CU Specifications

Operating method		Flatbed and ADF (automatic document feeder)
Image sensor		Colour CDD (charge-coupled device)
Light source		Cold cathode discharge tube (white)
Document size	Minimum	A6 (114mm x 140mm)
	Maximum	A4 (210 mm x 297 mm)
Output resolution		600 / 400 / 300 / 240 / 150 / 100 / 50dpi (selectable)
Optical resolution	ADF	600 dpi
	Flatbed	600 dpi
Scanning speed	Colour	3.3 ppm for A4 portrait format at 150 dpi
	Mono	10 ppm A4 portrait format at 200 dpi
Grayscale level	(internal)	256 levels
Image processing		Dither, Error diffusion
Capacity of ADF		Maximum 25 sheets, paper weight: 80 g/m ² , A4
Interface (selectable)		USB1.1
Image output format		Binary, Grayscale 8-bit, Colour 24-bit
Power requirements		100 to 240 VAC, 50/60 Hz
Power consumption		<20 watts
Operating environment		Temperature: 15°C - 35°C
Relative humidity		20% - 80%
Dimensions (WxDxH)		445 x 304 x 179 mm
Weight		4.9 kg
Recommended daily throughput		100 pages (5,000 hours MTBF)

Specifications are subject to change without notice. For the latest information, contact your local Fujitsu representative.

Fujitsu Europe Limited
 Hayes Park Central
 Hayes End Road
 Hayes Middlesex UB4 8FE
 England
 Tel: (+44-(0)20) 8573 4444
 Fax: (+44-(0)20) 8573 2643
 www.fel.fujitsu.com

Fujitsu Deutschland GmbH
 Frankfurter Ring 21 I
 80807 Munich
 Germany
 Tel: (+49-(0)89) 32378-0
 Fax: (+49-(0)89) 32378-100
 www.fdg.fujitsu.com

Fujitsu Italia S.p.A.
 Via Nazario Sauro, 38
 20099 Sesto San Giovanni (MI)
 Italy
 Tel: (+39) 0226294.1
 Fax: (+39) 0226294.201
 www.fis.fujitsu.com

